

# DEPARTMENT OF CIVIL ENGINEERING

TÜVRheinland

CERTIFIED

# PATENTS

S.No.	Name of the Inventor(s)	Name of the Applicant(s)	Title of the Patent	Patent Application No.	Date of filing	Patent Status	Date Published / Granted
		AC	ADEMIC YEAR: 2021 - 202	22			
1.	Dr. P. Subashree Dr. K. Akil	Hindusthan College of Engg. & Tech.	Manufacture of Rubcrete Slab	202241030766	30.05.2022	Published	10.06.2022
	ACADEMIC YEAR: 2022 - 2023						
2.	Mr. R. Sakthivel Mr. R. Parthasaarathi Mr. M. Dinesh Kumar Mr. V. Suresh	Hindusthan College of Engg. & Tech.	Metal Grinding Dust in Brick Manufacturing	202241038504	05.07.2022	Published	15.07.2022
3.	Ms. R. Priyadharshini Mr. R. Parthasaarathi Mr. R. Sakthivel Mr. V. Suresh	Hindusthan College of Engg. & Tech.	Precast Building Steel Tublerusing Waste Recycling	202241038506	05.07.2022	Published	15.07.2022
4.	Dr. K. Akil Mr. A. Alex Livingston Raja Ms. K. Saraswathi Mr. R. Senthil Kumar	Hindusthan College of Engg. & Tech.	Integration of Pitcher and Drip Irrigation Systems for Effective Water Management	202241038507	05.07.2022	Published	15.07.2022

S.No.	Name of the Inventor(s)	Name of the Applicant(s)	Title of the Patent	Patent Application No.	Date of filing	Patent Status	Date Published / Granted
5.	Dr. P. Subashree Dr. K. Akil Mr. S. Vivek Mr. K. Siddharth	Hindusthan College of Engg. & Tech.	Rubberized High Fracture Resistance Concrete Barrier for Highways	202241038508	05.07.2022	Published	15.07.2022
6.	Mr. R. Parthasaarathi Mr. R. Sakthivel Ms. R. Priyadharshini Mr. M. Dineshkumar	Hindusthan College of Engg. & Tech.	Fiber Reinforced Pre- Stressed Concrete Beam to Rebel Three Load Factor	202241038509	05.07.2022	Published	15.07.2022
7.	Dr. K. Akil Mr. R. Sakthivel Ms. R. Sakthi Shree Mr. Bhrugumalla Manoj Ms. Gottupalli Ramya	Hindusthan College of Engg. & Tech.	Reuse of Non-Biodegradable Solid Waste as a Partial Replacement of Fine Aggregate in Concrete Blocks	202241043238	28.07.2022	Published	05.08.2022

## (19) INDIA

(22) Date of filing of Application :30/05/2022

(54) Title of the invention : MANUFACTURE OF RUBCRETE SLAB				
<ul> <li>(51) International classification</li> <li>(86) International Application No Filing Date</li> <li>(87) International Publication No</li> <li>(61) Patent of Addition to Application Number Filing Date</li> <li>(62) Divisional to Application Number Filing Date</li> <li>Filing Date</li> </ul>	:C04B0018220000, E01C0007260000, C08J0011100000, E01C0011000000, C04B0014020000 :NA :NA :NA : NA :NA :NA :NA :NA	<ul> <li>(71)Name of Applicant : <ul> <li>1)HINDUSTHAN COLLEGE OF ENGINEERING AND</li> <li>TECHNOLOGY</li> <li>Address of Applicant :VALLEY CAMPUS, POLLACHI</li> <li>HIGHWAY, COIMBATORE, TAMIL NADU, INDIA, PIN</li> <li>CODE-641032</li></ul></li></ul>		

## (57) Abstract :

Rubberized concrete (Rubcrete) is created from scrap rubber tyres with partial replacement of fine aggregates by crumb rubber. Waste rubber tyres are harmful to the environment and it is estimated that only 4% is used in civil engineering applications. As fine aggregates are available in limited quantity, waste tyres can be utilized for partial replacement of fine aggregates in concrete. Preliminary concrete properties with partial replacement of fine aggregates by pre-treated crumb rubber in amounts of 10%, 15%, and 20% of the total weight of fine aggregates and addition of rubber fibres in proportions of 1%, 1.5% and 2% of the total weight of coarse aggregates were examined for M25 grade concrete. Rubberized concrete specimens were tested for workability, compressive strength, split tensile strength and flexural strength. Optimum percentage of fine aggregate replacement with crumb rubber and optimum proportion of rubber fibres were arrived. With the optimum values arrived, specimens of size 300mm x 300mm x 50mm was cast and tested for impact load. The number of blows required for the first crack and total slab collapse was determined. The characteristics were investigated. Hybrid rubberized concrete slab made of two layers, with rubber concrete on top and normal concrete is used as the bottom layer as it has better tensile strength. The energy absorption and ductility index of hybrid rubberized concrete slabs were found to be higher and showed better results. This hybrid rubberized concrete can be used where concrete surfaces are subjected to high impact loads such as roads, machine floors, etc. thereby improving the quality and performance of the surfaces.

(22) Date of filing of Application :05/07/2022

(54) Title of the invention : METAL GRINDING DUST IN BRICK MANUFACTURING

<ul> <li>(51) International classification</li> <li>(86) International Application No Filing Date</li> <li>(87) International Publication No</li> <li>(61) Patent of Addition to Application Number Filing Date</li> <li>(62) Divisional to Application Number Filing Date</li> </ul>	:B28B0015000000, B28B0007000000, G06Q0010100000, B29L0031000000, B28B0001087000 :NA :NA :NA :NA :NA :NA :NA	<ul> <li>(71)Name of Applicant :</li> <li>1)HINDUSTHAN COLLEGE OF ENGINEERING AND TECHNOLOGY <ul> <li>Address of Applicant :HINDUSTHAN COLLEGE OF</li> <li>ENGINEERING AND TECHNOLOGY, VALLEY CAMPUS,</li> <li>POLLACHI HIGHWAY, COIMBATORE, TAMILNADU,</li> <li>INDIA 641032</li></ul></li></ul>
---	--	---

(57) Abstract :

Annexure-3 The fundamentals of brick manufacturing have not changed over time.. However, technological advancements have made contemporary brick plants substantially more efficient and have improved the overall quality of the products. A more complete knowledge of raw materials and their properties, better control of firing, improved kiln designs and more advanced mechanization have all contributed to ' advancing the brick industry. Other Technical Notes in this series address the classification and selection of brick considering the use, exposure and required durability of the finished brickwork.

(22) Date of filing of Application :05/07/2022

<ul> <li>(51) International classification</li> <li>(86) International Application No Filing Date</li> <li>(87) International Publication No</li> <li>(61) Patent of Addition to Application Number Filing Date</li> <li>(62) Divisional to Application Number Filing Date</li> </ul>	:E04B0005040000, G06Q0050080000, G06Q0010060000, G06Q0010000000, B28B0015000000 :NA :NA :NA :NA :NA :NA :NA :NA :NA	<ul> <li>(71)Name of Applicant : <ul> <li>1)HINDUSTHAN COLLEGE OF ENGINEERING AND</li> <li>TECHNOLOGY</li> <li>Address of Applicant :HINDUSTHAN COLLEGE OF</li> <li>ENGINEERING AND TECHNOLOGY, VALLEY CAMPUS,</li> <li>POLLACHI HIGHWAY, COIMBATORE, TAMILNADU,</li> <li>INDIA 641032</li></ul></li></ul>
---	--	--

(54) Title of the invention : PRECAST BUILDING STEEL TUBLER USING WASTE RECYCLING

# (57) Abstract :

Annexure-3 The government of Malaysia has introduced Industrialized Building System (IBS) or commonly termed offsite construction in other countries to replace the conventional method of construction, as one of the initiatives to overcome the problems related to waste generation and negative environmental impact in the construction industry. There are few studies of the construction waste generation focus on-the offsite, particularly at precast production plant as compared to the construction site. This study aims to investigate the significant type of construction waste generated at precast concrete plants in Johor. In order to identify the type of waste generated in the process of manufacturing the precast concrete component, this study involved field observation to three precast concrete plants in Johor, together with analysing the selected organization's document on the waste generation and management record. Interviews were also conducted with the production man-ager/engineer to support the data collection process. The findings revealed that, the types of construction waste that commonly found in the precast concrete plants are concrete and steel. The most significant type of waste generated at precast concrete factory is concrete (total 1,298.56 tonnes for 3 factories, followed by 820 tonnes; 350 tonnes and 128.56 tonnes). This study provides useful information concerning waste assessment data to achieve a better understanding of construction waste in the precast concrete manufacturing industry.

(19) INDIA

MANAGEMENT

(22) Date of filing of Application :05/07/2022

(43) Publication Date : 15/07/2022

MANAGEMENT		
<ul> <li>(51) International classification</li> <li>(86) International Application No Filing Date</li> <li>(87) International Publication No</li> <li>(61) Patent of Addition to Application Number Filing Date</li> <li>(62) Divisional to Application Number Filing Date</li> </ul>	:A01G0025020000, C02F0001280000, A61K0038000000, C02F0001000000, A01G0025000000 :NA :NA :NA :NA :NA :NA :NA	(71)Name of Applicant : 1)HINDUSTHAN COLLEGE OF ENGINEERING AND TECHNOLOGY Address of Applicant :HINDUSTHAN COLLEGE OF ENGINEERING AND TECHNOLOGY, VALLEY CAMPUS, POLLACHI HIGHWAY, COIMBATORE, TAMILNADU, INDIA 641032

(54) Title of the invention : INTEGRATION OF PITCHER AND DRIP IRRIGATION SYSTEMS FOR EFFECTIVE WATER

(57) Abstract :

Annexure-3 Integration of drip irrigation with pitcher irrigation can be even more cost and time effective as they reduce the manual work of refilling the pitchers, especially when adopted for large areas. As two or more plants can be planted around the periphery of the pitcher, it can considerably reduce the number of laterals and emitters, thereby reducing the initial cost. Water requirement can be regulated based on the number of pitchers per acre, type of the crop grown-, available quality of water and filling schedule. The laterals of the drip can be drawn.below the ground level to reduce the physical damages and to increase the longevity of the pipes. Water stored in small tanks at a higher elevation can be used as a source for the drips to enable gravity flow thereby avoiding the usage of pumps. The pitchers have to be installed in such a way that its openings are at least a few inches above the ground level to prevent the entry of soil into it. The opening must be shut using an earthen lid after filling to prevent any loss of water due to evaporation. Organic fertilizers can be mixed and addedalong with the water if required.

(22) Date of filing of Application :05/07/2022

<ul> <li>(51) International classification</li> <li>(86) International Application No Filing Date</li> <li>(87) International Publication No</li> <li>(61) Patent of Addition to Application Number Filing Date</li> <li>(62) Divisional to Application Number Filing Date</li> </ul>	:C04B0018220000, B60C0001000000, G01N0003300000, B29B0017000000, G01N0003480000 :NA :NA :NA :NA :NA :NA :NA :NA	(71)Name of Applicant : 1)HINDUSTHAN COLLEGE OF ENGINEERING AND TECHNOLOGY Address of Applicant :HINDUSTHAN COLLEGE OF ENGINEERING AND TECHNOLOGY, VALLEY CAMPUS, POLLACHI HIGHWAY, COIMBATORE, TAMILNADU, INDIA 641032
---	---	---

(54) Title of the invention · RUBBERIZED HIGH FRACTURE RESISTANCE CONCRETE BARRIER FOR HIGHWAYS

#### (57) Abstract :

Annexure-3 Waste tyre disposal is currently a serious waste management issue around the world. It was discovered that there are 1.2 billions of waste tire rubber generated globally each year, with 11 percent of post-consumer tires being exported, 27 percent being sent to landfill, stockpiled, or illegally discarded, and only 4 percent being utilized for Civil Engineering projects. As a result, attempts have been made to identify waste tire applications in civil engineering. Rubberized Concrete was created in this study by casting several concrete mixes including varied % substitutions of coarse and fine crumb rubber for normal particles. The mechanical parameters of standard specimens formed of this rubberized concrete, such as compressive strength and elastic modulus values, were determined. It has been projected that the best % replacement of fine and coarse crumb rubber mix will be found. Experiments were carried out till the flexural characteristics of rubberized concrete slab specimens measuring 100 mm x 500 mm were well understood. To determine the influence of rubber on energy dissipation, 500 mm x 500 mm slabs were cast and put through dynamic Impact drop tests. The test findings were validated using an analytical model for flexural and impact strength. The finished product would be ideal for concrete safety barriers that require high strength, fracture resistance, and energy dissipation.

(22) Date of filing of Application :05/07/2022

<ul> <li>(51) International classification</li> <li>(86) International Application No Filing Date</li> <li>(87) International Publication No</li> <li>(61) Patent of Addition to Application Number Filing Date</li> <li>(62) Divisional to Application Number</li> </ul>	:E01D0101260000, E04C0005010000, E04C0005070000, F27D0001000000, E04C0005160000 :NA :NA :NA	<pre>(71)Name of Applicant :</pre>
		TECHNOLOGY, VALLEY CAMPUS, POLLACHI HIGHWAY, COIMBATORE, TAMILNADU, INDIA 641032

(57) Abstract :

Annexure-3 In general, prestressed concrete bridge beams are optimized In their cross-section dimensions to limit the dead weight of the structure. The slender web makes it even more difficult to place the. large amount of rebar's required for shear strength, confinement of concrete and anchorage zone reinforcement. Thus the anchorage .zone reinforcement becomes quite congested, which lends to difficulty in consolidating the concrete properly. Hence, the quality of concrete degrades at the end zones, again making it susceptible to cracking.' Moreover, it is also labor-intensive to produce and place the large amount of steel reinforcement in the end zone.

(12) PATENT APPLICATION PUBLICATION (19) INDIA

(22) Date of filing of Application :28/07/2022

## (54) Title of the invention : REUSE OF NON-BIODEGRADABLE SOLID WASTE AS A PARTIAL REPLACEMENT OF FINE AGGREGATE IN CONCRETE BLOCKS

		(71)Name of Applicant :
		1)HINDUSTHAN COLLEGE OF ENGINEERING AND
		TECHNOLOGY
		Address of Applicant :HINDUSTHAN COLLEGE OF
		ENGINEERING AND TECHNOLOGY, VALLEY CAMPUS,
		POLLACHI HIGHWAY, COIMBATORE, TAMIL NADU,
		INDIA - 641032
		Name of Applicant : NA
		Address of Applicant : NA
		(72)Name of Inventor :
		1)Dr. K. AKIL
	C04D00000000000000000000000000000000000	Address of Applicant : PROFESSOR & HEAD/CIVIL,
(51) International	:C04B0028020000, C04B0018160000,	HINDUSTHAN COLLEGE OF ENGINEERING AND
classification	G01N0033380000, C04B0018220000,	TECHNOLOGY, VALLEY CAMPUS, POLLACHI HIGHWAY,
	B09B0003000000	COIMBATORE, TAMIL NADU, INDIA - 641032
(86) International	:NA	
Application No	:NA	2)Mr. SAKTHIVEL R
Filing Date		Address of Applicant :ASSISTANT PROFESSOR/CIVIL,
(87) International	: NA	HINDUSTHAN COLLEGE OF ENGINEERING AND
Publication No		TECHNOLOGY, VALLEY CAMPUS, POLLACHI HIGHWAY,
(61) Patent of Addition	n:NA	COIMBATORE, TAMIL NADU, INDIA - 641032
to Application Numbe	rr:NA	
Filing Date		3)Ms. SAKTHI SHREE R
(62) Divisional to	:NA	Address of Applicant :HINDUSTHAN COLLEGE OF
Application Number	:NA	ENGINEERING AND TECHNOLOGY, VALLEY CAMPUS,
Filing Date		POLLACHI HIGHWAY, COIMBATORE, TAMIL NADU,
		INDIA - 641032
		4)Mr. BHRUGUMALLA MANOJ
		Address of Applicant :HINDUSTHAN COLLEGE OF
		ENGINEERING AND TECHNOLOGY, VALLEY CAMPUS,
		POLLACHI HIGHWAY, COIMBATORE, TAMIL NADU,
		INDIA - 641032
		5)Ms. GOTTUPALLI RAMYA
		Address of Applicant :HINDUSTHAN COLLEGE OF
		ENGINEERING AND TECHNOLOGY, VALLEY CAMPUS,
		POLLACHI HIGHWAY, COIMBATORE, TAMIL NADU,
		INDIA - 641032
(57) Abstract ·		

# (57) Abstract :

The disposal of non-biodegradable solid waste is a major problem in developing countries. The non-biodegradable solids (PET, PP, PVC, etc.) which cause considerable environmental impacts are to be recycled and reused. Various researches have been done to reuse the solid waste in various forms. This study includes the reuse of non-biodegradable solid waste as a partial replacement of Fine Aggregate in the manufacturing of Solid Concrete Blocks. The solid waste was crushed to a diameter less than 4.75mm and used as a partial replacement of fine aggregate (m-sand) in different proportions as 5%, 10%, 15%, 20%, and 25% in MI5 grade concrete. Conventional mix with and without 10% Alccofine-1203 mineral was tested. Conplast SP430of 1.5% by weight of cement was added as water reducing admixture. In the mix with Alccofine, plastic granules in the proportions mentioned above were added and concrete blocks were cast. The properties of solid waste (Mainly PVC) used as fine aggregates i.e., particle size distribution, specific gravity, etc., and the properties of concrete i.e., workability, compressive strength and flexural strength were determined.